


Double Pole	A	B	C	D	ØR	Power
LGT.50.204.10	3000	1980	100	150	415	2 x 28 W
LGT.50.204.11	4000	1980	100	150	415	2 x 36 W
LGT.50.204.12	5000	1980	100	150	415	2 x 56 W
LGT.50.204.13	6000	1980	100	200	415	2 x 72 W
LGT.50.204.14	7000	1980	100	200	415	2 x 72 W
LGT.50.204.15	8000	1980	100	200	415	2 x 108 W

* Dimensions are millimeter(mm)



Product Description

- Corrosion resistant aluminium body
- Natural wood coating
- Very thin real teak tree
- Anchorage unit with galvanized
- Chromate conversion pretreatment
- Electrostatic powder coating
- Stainless steel screws (grade 304)
- Mechanical impact resistance IK08
- Protection Grade IP66
- Electrical installation Class I

LED & Optics

- Up to 130 lm/w
- 3000K - 4000K - 6500K
- 220-240(V) 50-60(Hz)

Options

- DALI controllable

Color Options

- RAL 7016 Anthracite Grey
- RAL 9005 Black
- RAL 9006 White Aluminium
- RAL 7022 Umbra Grey
- RAL 9016 White
- RAL xxxx Optional