



	A	BxC	D	Power
LGT.10.105.01	4000	100x150	1600	35W + 35W
LGT.10.105.02	5000	100x150	1700	70W + 35W
LGT.10.105.03	6000	100x200	1850	70W + 35W



### Product Description

- Corrosion resistant aluminum body
- PMMA Lens Diffuser
- Mechanical impact resistance IK08
- Protection Grade IP66
- Chromate conversion pretreatment
- Electrostatic powder coating
- Stainless steel screws (grade 304)
- Electrical installation Class I
- Poles are supplied without anchor set
- Flange cover can be ordered separately.

### Options

- DALI controllable

### Technical Details

- Module luminous efficiency : 135 lm/W
- Luminaire luminous efficiency : 116 lm/W (4000k)
- Input Voltage-Frequency: 220-240(V) 50-60(Hz)
- Cct : 2700K - 3000K - 4000K - 6500K
- Color Rendering Index : >80
- Led Life Time - L70 : > 60.000 hours @Ta= 45 °C
- Operating Temperature Range : -20 °C / +45 °C
- Control Systems: On/Off / DALI

### Color Options

- RAL 7016 Anthracite Grey
- RAL 9005 Black
- RAL 9006 White Aluminium
- RAL 7022 Umbra Grey
- RAL 9016 White
- RAL xxxx Optional